


I-V Curves

I-V Curves of PV module CSG200W at different light power




Typical Electrical Characteristics

Solar cells:	Mono-Crystalline 156X156mm 48 pcs (6x8) — 3 bus bars					
Max-power	195Wp	200Wp	205Wp	210Wp	215Wp	220Wp
Power Tolerance	0 to +6W					
Voltage at Pmax (Vmp)	24.4V	24.5V	24.6V	24.8V	25.0V	25.2V
Current at Pmax (Imp)	8.0A	8.16A	8.37A	8.48A	8.60A	8.63A
Open-Circuit Voltage (Voc)	29.8V	29.9V	30.0V	30.3V	30.5V	31.1V
Short-Circuit Current (Isc)	8.66A	8.83A	9.06A	9.2A	9.31A	9.34A
Max-System Voltage (VDC)	1000V(IEC), 600V(UL)					
Cell Efficiency	17.2%	17.6%	18.2%	18.6%	18.9%	19.4%
Module Efficiency	14.8%	15.2%	15.6%	16.0%	16.4%	16.8%
No. of Bypass Diodes (pcs.)	3					
Max. Series Fuse (A)	12A					
Temperature Coefficient of Pmax	-0.45%/°C					
Temperature Coefficient of Voc	-0.34%/°C					
Temperature Coefficient of Isc	0.05%/°C					
Nominal Operating Cell Temperature	45±2°C					

*STC Conditions (1000W/m²; 1.5 AM and 25°C Cell temperature)

Dimensions



Mechanical Characteristics

Cable type, Cross-sectional area and Length	Φ=4mm ² , L=1000±5mm
Type of Connector	Compatible type MC4
Dimension A×B×C	1324×992×45mm (52.13×39.06×1.77 inch)
Weight	16.0kg (35.2lb)
No. of Draining Holes In Frame	16
Construction	Glass: High Transmission, Low Iron, Tempered Glass 3.2mm Encapsulation: EVA Back side: White
Junction Box (protection degree)	IP 67
Frame	Clear anodized aluminum alloy type 6063T5 frame

Qualification Test Parameters

Dielectric Insulation Voltage	6000V DC max
Operating Temperature	-40°C to +85°C
Max load	5400Pa
Hailstone impact	25mm (1inch) at 23m/s (52mph)
Tire safety class	Class C

Packaging Configuration

Packaging Configuration	22pcs./box and 2pcs./box	
Quantity of Big Box/Pallet	1box/pallet	1 boxes/pallet
Quantity of Small Box/Pallet	/	9 boxes/pallet
Loading Capacity	704pcs./40'HQ	320pcs./20'GP

► Caution: Read Safety And Installation Instructions Before Using This Product